

JIS シームレス鋼管

SUS304											
材質											
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
2	0.5	2000	0.019	TP	C	6.35	1.2	4000	0.154	TP	C
2.5	0.5	2000	0.025	"	"		1.5	2000	0.181	"	"
3	0.5	2000	0.031	"	"			4000		"	"
	1	2000					0.081	"	"		
3.18	0.5	2000	0.033	"	"			4000		"	"
	1	2000	0.05	"	"		1	2000	0.149	"	"
4	0.5	2000	0.044	"	"			4000		"	"
	1	2000	0.075	"	"		1.5	4000	0.206	"	"
5	0.5	2000	0.056	"	"		2	4000	0.249	"	"
	1	2000	0.1	"	"	8	0.5	2000	0.093	"	"
		4000		"	"			4000		"	"
	1.5	2000	0.131	"	"		0.8	2000	0.143	"	"
		4000		"	"			4000		"	"
6	0.3	2000	0.043	"	"		1	2000	0.174	"	"
	0.5	2000		"	"			4000		"	"
		4000	0.069	"	"		1.2	2000	0.203	"	"
6	0.8	2000	0.104	"	"			4000		"	"
		4000		"	"		1.5	2000	0.243	"	"
	1	2000	0.125	"	"			4000		"	"
		4000		"	"		2	2000	0.299	"	"
	1.5	2000	0.168	"	"			4000		"	"
		4000		"	"		2.5	2000	0.343	"	"
	2	2000	0.199	"	"			4000		"	"
		4000		"	"	9	0.5	2000	0.106	"	"
6.35	0.5	2000	0.073	"	"			4000		"	"
		4000		"	"		1	2000	0.199	"	"
	0.71	2000	0.1	"	"			4000		"	"
		4000		"	"		1.5	4000	0.28	"	"
	0.89	2000	0.121	"	"		2	4000	0.349	"	"
		4000		"	"		2.5	2000	0.405	"	"
	1	2000	0.133	"	"			4000		"	"
		4000		"	"	9.53	0.5	2000	0.112	"	"

JIS シームレス鋼管

SUS304												
材質												
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	
9.53	0.5	4000	0.112	TP	C	10.5	1.2	2000	0.278	TP	C	
	0.89	2000	0.192	"	"				4000		"	"
		4000		"	"			1.5	4000	0.336	"	"
	1	2000	0.212	"	"				5500		"	"
		4000		"	"			1.7	2000	0.373	"	"
	1.2	4000	0.249	"	"				4000		"	"
	1.25	2000	0.258	"	"				5500		"	"
		4000		"	"			2	2000	0.423	"	"
	1.5	2000	0.318	"	"				4000		"	"
		4000		"	"			2.4	2000	0.484	"	"
	1.65	4000	0.324	"	"				4000		"	"
	1.7	4000	0.332	"	"				5500		"	"
	2	4000	0.375	"	"							
10	0.5	2000	0.118	"	"	11	0.5	4000	0.131	"	"	
		4000		"	"			1	2000	0.249	"	"
	0.8	2000	0.183	"	"				4000		"	"
		4000		"	"			1.5	2000	0.355	"	"
	1	2000	0.224	"	"			4000		"	"	
		4000		"	"	12	0.5	4000	0.143	"	"	
	1.2	2000	0.263	"	"			0.8	4000	0.223	"	"
		4000		"	"			1	2000	0.274	"	"
	1.5	2000	0.318	"	"				4000		"	"
		4000		"	"			1.2	4000	0.323	"	"
	2	2000	0.399	"	"			1.5	2000	0.392	"	"
		4000		"	"				4000		"	"
	2.5	2000	0.467	"	"			2	2000	0.498	"	"
	4000		"	"				4000		"	"	
3	2000	0.523	"	"		2.5	4000	0.592	"	"		
	4000		"	"		3	2000	0.673	"	"		
10.5	0.5	2000	0.125	"	"			4000	0.797	"	"	
		4000		"	"	12.7	0.5	4000	0.152	"	"	
	1	4000	0.237	"	"			0.89	4000	0.262	"	"

JIS シームレス鋼管

SUS304											
材質											
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
12.7	1	2000	0.291	TP	C	14	1	4000	0.324	TP	C
		4000		"	"			1.2	4000	0.383	"
	1.24	4000	0.354	"	"		1.5	4000	0.467	"	"
		1.5	4000	0.418	"			"	2	2000	0.598
	1.65		4000	0.454	"		"	2.5		4000	
		2	2000	0.533	"		"		3	4000	0.716
	3		4000		"		"	4		4000	0.822
		4000		0.725	"		"				0.996
13	0.5		4000	0.156	"	"	15	0.5	2000	0.181	"
		4000		"	"	1			2000	0.349	"
	1	2000	0.299	"	"			1.2	4000	0.413	"
		2	4000	0.548	"	"			1.5	2000	0.504
	2.5		2000	0.654	"	"		2		2000	0.648
		3	2000	0.747	"	"					
	4000				"	"					"
		13.8	1	4000	0.319	"		"	15.88	1	4000
4000				"	"	1.5	4000	0.537			"
1.2	4000		0.377	"	"		0.5	4000		0.193	"
	1.65		2000	0.499	"	"		1		2000	0.374
4000					"	"	1.2			4000	0.422
	5500				"	"		1.5		4000	0.542
2			2000	0.588	"	"	2			2000	0.697
	4000				"	"					
2.2		4000	0.636	"	"				"	"	
	3	2000	0.807	"	"				"	"	
4000				"	"				"	"	
	5500			"	"				"	"	
4		4000	0.976	"	"				"	"	
	14	0.5	2000	0.168	"	"				"	"
4000				"	"	2.5	4000	0.841	"	"	
1		2000	0.324	"	"		3	2000	0.971	"	"

JIS シームレス鋼管

SUS304											
材質											
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
16	3	4000	0.971	TP	C	19	1.65	4000	0.713	TP	C
	4	4000	1.2	"	"		2	4000	0.847	"	"
	5	2000	1.37	"	"		2.5	4000	1.03	"	"
		4000		"	"		3	4000	1.2	"	"
17	1	4000	0.399	"	"	20	4	4000	1.49	"	"
	1.5	4000	0.579	"	"		0.5	4000	0.243	"	"
	2	4000	0.747	"	"		1	4000	0.473	"	"
17.3	1.2	2000	0.481	"	"		1.5	4000	0.691	"	"
		4000		"	"	2	2000	0.897	"	"	
	1.5	4000	0.59	"	"		4000		"	"	
	1.65	4000	0.643	"	"	2.5	4000	1.09	"	"	
	2	2000	0.762	"	"	3	2000	1.27	"	"	
		4000		"	"		4000		"	"	
		5500		"	"	4	2000	1.59	"	"	
	2.3	2000	0.859	"	"		4000		"	"	
		4000		"	"	5	2000	1.87	"	"	
		5500		"	"		4000		"	"	
18	3.2	2000	1.12	"	"	21.7	1.2	4000	0.613	"	"
		4000		"	"		1.5	4000	0.755	"	"
		5500		"	"		1.65	4000	0.824	"	"
		5500		"	"			5500		"	"
	0.5	4000	0.218	"	"		2.1	4000	1.03	"	"
	1	4000	0.423	"	"		2.5	4000	1.2	"	"
	1.5	4000	0.617	"	"		5500		"	"	
	2	4000	0.797	"	"		6000		"	"	
19	2.5	2000	0.965	"	"		2.8	4000	1.32	"	"
		4000		"	"		5500		"	"	
	3	4000	1.12	"	"		6000		"	"	
	4	4000	1.39	"	"		3.7	4000	1.66	"	"
		4000		"	"		5500		"	"	

JIS シームレス鋼管

SUS304												
材質												
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	
21.7	4.7	4000	1.99	TP	C	25.4	3	4000	1.67	TP	C	
		5500		"	"			4	4000	2.13	"	"
	7.5	4000	2.65	"	"		4.5		4000	2.34	"	"
		5500		"	"			26	1.5	4000	0.915	"
22	0.5	4000	0.268	"	"	3	4000			1.72	"	"
		1	4000	0.523	"		"	27.2	1.2	4000	0.777	"
	1.5	4000	0.766	"	"	1.5	4000			0.96	"	"
	2	4000	0.996	"	"		1.65		4000	1.05	"	"
	2.5	4000	1.21	"	"	2.1			5500		"	"
	3	4000	1.42	"	"		4000		1.31	"	"	
	4	4000	1.79	"	"	5500			"	"		
	23	1	4000	0.548	"	"	2.5	4000	6000		"	"
1.5			4000	0.803	"	"			4000	1.54	"	"
2		4000	1.05	"	"	2.9	4000	5500		"	"	
		3	4000	1.49	"			"	6000		"	"
24	2	4000	1.1	"	"	4000	1.76	"	"			
		4	4000	1.99	"		"	5500		"	"	
25	0.5	2000	0.305	"	"	3.9	4000	6000		"	"	
		1	4000	0.598	"			"	4000	2.26	"	"
	1.5	4000	0.878	"	"	4.5	4000	5500		"	"	
		2	4000	1.15	"			"	6000		"	"
	2.5	4000	1.4	"	"	5.5	4000	5500	2.54	"	"	
	3	4000	1.64	"	"			4000	2.97	"	"	
	4	4000	2.09	"	"	6	4000	5500		"	"	
	5	4000	2.49	"	"			6000		"	"	
	5.5	4000	2.67	"	"	7.8	4000	4000	3.17	"	"	
	6	4000	2.84	"	"			4000	3.77	"	"	
25.4	1	4000	0.608	"	"	5500	28	1	4000	0.673	"	"
		1.2	4000	0.723	"				"	1.5	4000	0.99
	1.5	4000	0.893	"	"	2	4000	1.3	"		"	
		2	4000	1.17	"		"	3	4000	1.87	"	"
	2.5	4000	1.43	"	"							

JIS シームレス鋼管

SUS304											
材質											
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
28	4.2	5500	2.49	TP	C	34	2	4000	1.59	TP	C
	5	4000	2.86	"	"		2.8	4000	2.18	"	C/H
	6.5	4000	3.48	"	"			5500		"	H
	7.5	4000	3.83	"	"			6000		"	"
29	2	4000	1.35	"	"	3	4000	2.32	"	"	
	3	4000	1.94	"	"			5500		"	"
30	1	4000	0.722	"	"			6000		"	"
	1.5	4000	1.06	"	"	3.4	4000	2.59	"	"	
	2	4000	1.39	"	"			5500	2.59	"	"
	2.5	4000	1.71	"	"		6000		"	"	
	3	4000	2.02	"	"	4	4000	2.99	"	"	
	3.5	4000	2.31	"	"		4.5	4000	3.31	"	"
	4	4000	2.59	"	"		5500		"	"	
	5	4000	3.11	"	"		6000		"	"	
	6	4000	3.59	"	"	5	4000	3.61	"	"	
8	4000	4.38	"	"	6.4		4000	4.4	"	"	
32	1	4000	0.722	"	"			5500		"	"
	1.2	4000	0.921	"	"	9.1	4000	5.64	"	C	
	1.5	4000	1.14	"	"			5500		"	C
	2	4000	1.49	"	"	35	2.5	4000	2.02	"	"
	2.5	4000	1.84	"	"		3	4000	2.39	"	H
	3	4000	2.17	"	"	36	2	4000	1.69	"	C
	3.5	4000	2.48	"	"		3	4000	2.47	"	H
	4	4000	2.79	"	"		4	4000	3.19	"	"
	4.5	4000	3.08	"	"		5	4000	3.86	"	C/H
	5	4000	3.36	"	"		5.5	4000	4.18	"	H
6	4000	3.89	"	"	6.5		4000	4.78	"	"	
7	4000	4.36	"	"	10		4000	6.48	"	C	
8	4000	4.78	"	"	38		1	4000	0.922	"	"
34	1	4000	0.822	"		"	1.2	4000	1.1	"	"
	1.5	4000	1.21	"		"	1.5	4000	1.36	"	"
	1.65	4000	1.33	"	"	2	4000	1.79	"	"	

JIS シームレス鋼管

SUS304												
材質												
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	
38	3	4000	2.62	"	H	42.7	3	6000	2.97	TP	H	
	3.5	4000	3.01	"	"		3.6	4000	3.51	"	"	
	4	4000	3.39	"	"			5500		"	"	
	4.5	4000	3.76	"	"			6000		"	"	
	5	4000	4.11	"	"		4	4000	3.86	"	"	
	5.5	5500	4.45	"	C		4.9	4000	4.61	"	"	
	6	4000	4.78	"	H			5500		"	"	
	7	4000	5.41	"	"			6000		"	"	
	8	4000	5.98	"	"		6	4000	5.49	"	"	
	9	4000	6.5	"	"		6.4	4000	5.79	"	"	
10	4000	6.97	"	C		5500		"	"			
40	1	4000	0.971	"	"		7.1	4000	6.3	TP	H	
	1.5	4000	1.44	"	"		8	4000	6.92	"	"	
	2	4000	1.89	"	"		9.1	4000	7.62	"	"	
	3	4000	2.77	"	H		10	4000	8.15	"	"	
	3.5	4000	3.18	"	"	45	1.5	4000	1.63	"	C	
	4	4000	3.59	"	"		2	4000	2.14	"	"	
	5	4000	4.36	"	"		3	4000	3.14	"	H	
	6	4000	5.08	"	"		4	4000	4.09	"	"	
	7	4000	5.75	"	"		5	4000	4.98	"	"	
	8	4000	6.38	"	"		5.5	4000	5.41	"	"	
9	4000	6.95	"	"	6		4000	5.83	"	"		
10	4000	7.47	"	"	6.5		4000	6.23	"	"		
41	1.5	4000	1.48	"	C			8	4000	7.37	"	"
	3	4000	2.84	"	"			10	4000	8.72	"	"
42.7	1.65	4000	1.69	"	"		11.5	4000	9.6	"	"	
	2	4000	2.03	"	"		12.5	4000	10.1	"	"	
	2.8	4000	2.78	"	H		6000		"	"		
		5500		"	"	46	5	4000	5.11	"	"	
	6000		"	"	48		7	4000	7.15	"	"	
	3	4000	2.97	"		"	48.6	1.65	4000	1.93	"	C
		5500		"	"	2		4000	2.32	"	"	

JIS シームレス鋼管

SUS304											
材質											
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
48.6	2.8	4000	3.19	TP	C/H	50.8	7	4000	7.64	TP	H
		5500		"	H		8	4000	8.53	"	"
	3	6000		"	"	10	4000	10.2	"	"	
		4000	3.41	"	"	12.5	6000	11.9	"	"	
	3.7	5500		"	"	14.5	4000	13.1	TK	"	
		6000		"	"	51	13	RL	12.3	"	"
	4	4000	4.14	"	"	52	3	4000	3.66	TP	"
		5500		"	"	6	4000	6.88	"	"	
	5.1	6000		"	"	7.5	4000	8.31	"	"	
		4000	4.44	"	"	10	4000	10.5	"	"	
	6	4000	5.53	"	"	53	13.5	RL	13.3	TK	"
		5500		"	"	54	1.65	4000	2.15	TP	C
	7.1	6000		"	"	2	4000	2.59	"	"	
		4000	6.37	TP	H	3	4000	3.81	"	H	
	8	4000	7.34	"	"	3.5	4000	4.4	"	"	
		5500		"	"	4	4000	4.98	"	"	
	10.2	4000	8.09	"	"	5	4000	6.1	"	"	
		4000	9.76	"	"	5.5	4000	6.64	"	"	
	50	6.5	4000	7.04	"	"	6	4000	7.17	"	"
		7	4000	7.5	"	"	9	4000	10.1	"	"
10		4000	9.96	"	"	13	4000	13.3	"	"	
12.5		4000	11.7	"	"	14	4000	13.9	"	"	
50.8	1.2	4100	1.48	"	C	55	2	4000	2.64	"	C
	1.5	4000	1.84	"	"		3	4000	3.89	"	C/H
	1.65	4000	2.02	"	"		5	4000	6.23	"	H
	2	4000	2.43	"	"		5.5	4000	6.78	"	"
	3	4000	3.57	"	H		8	4000	9.37	"	"
	4	4000	4.66	"	"	56	3	4000	3.96	"	"
	5	4000	5.7	"	"		8	4000	9.57	"	"
	5.5	4000	6.21	"	"		10	4000	11.5	"	"
	6	4000	6.7	"	"		14	4300	14.6	"	"
	6.5	4000	7.17	"	"		17	4000	16.5	"	"



JIS シームレス鋼管

SUS304											
材質											
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
57	2	4000	2.74	TP	C	60.5	7	4000	9.33	TP	H
	3	4000	4.04	"	H		8.7	4000	11.2	"	"
	4	4000	5.28	"	"			5500		"	"
	6	4000	7.62	"	"		10	4000	12.6	"	"
	7.5	4000	9.25	"	"		11.1	4000	13.7	"	"
	8	4000	9.76	"	"			5500		"	"
	10	4000	12	"	"		15	4000	17	"	"
60	7	4000	9.24	"	"	62	6.5	4000	8.99	"	"
	12.5	4000	14.8	"	"			5000		"	"
60.5	1.65	4000	2.42	TP	C	63	15.5	5010	18.3	"	"
		6000		"	"	63.5	1.65	4000	2.54	"	C
	2	4000	2.91	"	"		2	4000	3.06	"	"
	2.8	4000	4.02	"	C/H		3	4000	4.52	"	H
		5500		"	H		4	4000	5.93	"	"
		6000	4.02	"	"		5	4000	7.29	"	"
	3	4000	4.3	"	"		6.5	4000	9.23	"	"
		5500		"	"			5000		"	"
		6000		"	"		7	4000	9.85	"	"
	3.5	4000	4.97	"	"		8	4000	11.1	"	"
		5500		"	"		10	RL	13.3	"	"
		6000		"	"		11	4000	14.4	"	"
	3.9	4000	5.5	"	"			5500		"	"
		5500		"	"			RL		"	"
6000			"	"	11.5		RL	14.9	"	"	
4.3	5500	6.02	"	"		15	4000	18.1	"	"	
4.9	4000	6.79	"	"		RL		"	"		
5	4000	6.91	"	"	65	2	4000	3.14	"	C	
5.5	4000	7.54	"	"		3	4000	6.43	"	H	
	5500		"	"		4	4000	6.08	"	"	
	6000		"	"		5	4000	7.47	"	"	
	6000		"	"		6	4000	8.82	"	"	
6	4000	8.15	"	"							

JIS シームレス鋼管

SUS304											
材質											
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
65	8	4000	11.4	TP	H	73	5.2	4000	8.78	TP	H
	10	4000	13.7	"	"		7	4000	11.5	"	"
	12	4000	15.8	"	"		9.3	4000	14.8	"	"
	14.5	5000	18.2	"	"		9.5	4000	15	"	"
	15	4000	18.7	"	"		10	4000	15.7	"	"
	20	5500	22.4	"	"			RL		"	"
67	4	4000	6.28	"	"	74	15	RL	21.7	"	"
	14.5	RL	19	TK	"		12	4010	18.5	"	"
68	6	4000	9.27	TP	"	75	10	4000	16.2	"	"
	7	RL	10.6	"	"		12.5	5500	19.5	"	"
	8	RL	12	"	"		17.5	5010	25.1	"	"
	13	4500	17.8	"	"	76.3	2.1	4000	3.88	"	C
69	9	4000	13.5	"	"		3	4000	5.48	"	C/H
		5500		"	"			5500		"	H
70	2	4000	3.39	"	C			6000		"	"
	3	4000	5.01	"	H	3.5	4000	6.35	"	"	
	4	4000	6.58	"	"		5500		"	"	
	5	4000	8.1	"	"		6000		"	"	
	6	4000	9.57	"	"	4	4000	7.2	"	"	
	6.5	4000	10.3	"	"		5500		"	"	
	7	4000	11	"	"	5.2	4000	9.21	"	"	
	8	4000	12.4	"	"		5500		"	"	
	10	6000	14.9	"	"	6	4000	10.5	"	"	
	12	4000	17.3	"	"		7	4000	12.1	"	"
	12.5	4000	17.9	"	"	7	4000	12.1	"	"	
	15	RL	20.6	"	"		5500		"	"	
	20	6500	24.9	"	"		6000		"	"	
	71	10.5	4000	15.8	"	"	8	4000	13.6	"	"
14		4000	19.9	"	"	9.5		4000	15.8	"	"
72	13	4000	19.1	"	"		5500		"	"	
	14	RL	20.2	"	"	10	4000	16.5	"	"	
73	3	4000	5.23	"	"		11	5500	17.9	"	"

JIS シームレス鋼管

SUS304												
材質												
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	
76.3	12.5	4000	19.9	TP	H	85	15	RL	26.2	TP	H	
	13.5	4000	21.1	"	"		16.5	5000	28.2	"	"	
		5000		"	"		20	RL	32.4	"	"	
	14	5400	21.7	"	"		25	RL	37.4	"	"	
		15	5000	22.9	"	"	89.1	2.1	4000	4.55	"	C
		16	4000	24	"	"			6000		"	"
		18	4900	26.1	"	"		3	4000	6.43	"	C/H
		20	4000	28	"	"			5500		"	H
		24	5230	31.3	"	"			6000		"	"
		78	16.5	5500	25.3	"		"	4	4000	8.48	"
80	2	4000	3.89	"	C				5500		"	"
	3	4000	5.75	"	H				6000		"	"
	4	4000	7.57	"	"	5.5		4000	11.5	"	"	
	5	4000	9.34	"	"				5500		"	"
	6	4000	11.1	"	"			6000		"	"	
	8	4100	14.3	"	"	6.6	4000	13.6	"	"		
	10	6000	17.4	"	"	7.6	4000	15.4	"	"		
	12	RL	20.3	"	"			5500		"	"	
	15	RL	24.3	"	"			6000		"	"	
	17.5	5000	27.2	"	"	11.1	4000	21.6	"	"		
	20	RL	29.9	"	"			5500		"	"	
	25	RL	34.3	"	"	15.2	5500	28	"	"		
82.6	3	4000	5.95	"	"	90	10	4000	19.9	"	"	
	5.5	RL	10.6	"	"		13.5	RL	25.7	"	"	
	7	4000	13.2	"	"		15	RL	28	"	"	
	8	4000	14.9	"	"		20	4000	34.9	"	"	
83	8.5	RL	15.7	"	"	25	RL	40.5	"	"		
85	4	4000	8.07	"	"	95	4	6000	9.07	"	"	
	8	RL	15.3	"	"		7.5	4000	16.3	"	"	
	10	RL	18.7	"	"		10	RL	21.2	"	"	
	12	RL	21.8	"	"		12.5	5000	25.7	"	"	
	12.5	RL	22.6	"	"		13	4000	26.6	"	"	

JIS シームレス鋼管

SUS304												
材質												
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	
95	15	4300	29.9	TP	H	106	13	4000	30.1	TP	H	
	16	4000	31.5	"	"		18	RL	39.5	"	"	
	17.5	4000	33.8	"	"		20	RL	42.8	"	"	
	20	4000	37.4	"	"		25	RL	50.4	"	"	
		4030			TK	"	108	10	RL	24.4	"	"
	22.5	RL	40.6	TP	"	110	10	RL	24.9	"	"	
	25	RL	43.6	"	"		13	RL	31.4	"	"	
98	13	RL	27.5	"	"		15	RL	35.5	"	"	
	15	RL	31	"	"	20	RL	44.8	"	"		
100	10	RL	22.4	"	"	114.3	2.1	4000	5.87	"	C	
	14.5	RL	30.9	"	"		3	4000	8.32	"	C/H	
	15	RL	31.8	"	"			5500		"	H	
	17.5	RL	36	"	"			6000		"	"	
	20	RL	39.9	"	"		4	4000	11	"	"	
101.6	2.1	4000	5.2	"	C			5500		"	"	
		6000		"	"			6000		"	"	
	3	4000	7.37	"	H	6	4000	16.2	"	"		
		5500		"	"		5500		"	"		
	4	4000	9.72	"	"		6000		"	"		
		5500		"	"	8.6	4000	22.6	"	"		
	5.7	4000	13.6	"	"		5500		"	"		
		5500		"	"		6000		"	"		
	7	4000	16.5	"	"	11.1	4000	28.5	"	"		
	8.1	4000	18.9	"	"	13.5	4000	33.9	"	"		
		5500		"	"	17.1	4000	41.4	"	"		
	11	4000	24.8	"	"	18	4000	43.2	"	"		
	12.7	4000	28.1	"	"	20	RL	47	"	"		
	15	RL	32.4	"	"	30	RL	63	"	"		
	20	4000	40.7	"	"	116	18	RL	43.9	"	"	
22.5	RL	44.3	"	"	118		14	RL	36.3	"	"	
25	RL	47.7	"	"			23.5	RL	55.3	"	"	
106	10	5000	23.9	"	"	120	4	6000	11.6	"	"	

JIS シームレス鋼管

SUS304												
材質												
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	
120	5	6000	14.3	TP	H	135	10	RL	31.1	TP	〃	
	8	4000	22.3	〃	〃		15	RL	44.8	〃	〃	
	10	RL	27.4	〃	〃		20	RL	57.3	〃	〃	
	13	4000	34.6	〃	〃		139.8	2.8	4000	9.56	〃	C
		RL		〃	〃			3.4	4000	11.6	〃	〃
	15	RL	39.2	〃	〃			5	4000	16.8	〃	H
	20	RL	49.8	〃	〃				5500		〃	〃
	25	RL	59.2	〃	〃				6000		〃	〃
	30	RL	67.3	TK	〃		6.6	4000	21.9	〃	〃	
122.5	6.5	RL	18.8	TP	〃		5500		〃	〃		
	8.6	RL	24.4	〃	〃	9.5	4000	30.8	〃	〃		
	25	RL	60.7	TK	〃		5500		〃	〃		
125	5	4000	14.9	TP	〃	12.7	4000	40.2	〃	〃		
	10	RL	28.6	〃	〃	15.9	4000	49.1	〃	〃		
	12.5	5000	35	〃	〃	22	RL	64.6	〃	〃		
	15	RL	41.1	〃	〃	140	10	4000	32.4	〃	〃	
	20	RL	52.3	〃	〃		14	RL	43.9	〃	〃	
	22.5	RL	57.4	〃	〃		20	RL	59.8	〃	〃	
					25		RL	71.6	〃	〃		
127	5	RL	15.2	〃	〃	30	RL	82.2	〃	〃		
	8	RL	23.7	〃	〃	35	RL	91.5	〃	〃		
	10	RL	29.1	〃	〃							
130	10	4000	29.9	〃	〃	145	10	RL	33.6	〃	〃	
	12.5	4000	36.6	〃	〃		12.5	4000	41.3	〃	〃	
	15	RL	43	〃	〃		15	4000	48.6	〃	〃	
	20	RL	54.8	〃	〃		20	RL	62.3	〃	〃	
	25	RL	65.4	〃	〃	150	7	RL	24.9	〃	〃	
132	10	4000	30.4	〃	〃		10	RL	34.9	〃	〃	
	13	RL	38.5	〃	〃		12.5	RL	42.8	〃	〃	
	15	RL	43.7	〃	〃		15	RL	50.4	〃	〃	
	21	RL	58.1	〃	〃		20	RL	64.8	〃	〃	
	26	RL	68.7	〃	〃	22.5	RL	71.5	〃	〃		
	30.5	RL	77.1	TK	〃	25	RL	77.8	〃	〃		

JIS シームレス鋼管

SUS304														
材質														
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上			
150	30	RL	89.7	TP	H	170	15	RL	57.9	TK	H			
	35	RL	100	"	"		20	RL	74.7	"	"			
152	15	RL	51.2	TK	"	180	26	RL	93.3	"	"			
	22.5	RL	72.6	TK	"		30	RL	105	TP	"			
152.4	10	4000	35.5	TP	"	185	10	RL	42.3	"	"			
155	10	RL	36.1	"	"		15	RL	61.7	TK	"			
	12	RL	42.7	"	"		20	RL	79.7	"	"			
	15	RL	52.3	"	"		25	RL	96.5	"	"			
	20	RL	67.3	"	"		30	RL	112	"	"			
	25	RL	81	TK	"		188	46	RL	163	TP	"		
160	10	4000	37.4	TP	"	190	15	RL	65.4	TK	"			
	15	RL	54.2	"	"		20	RL	84.7	"	"			
	20	RL	69.7	"	"		30	RL	120	"	"			
	22	RL	75.6	TK	"	200	10	RL	47.3	"	"			
	26	RL	86.8	TP	"		15	RL	69.1	"	"			
	30	RL	97.1	TK	"		20	RL	89.7	"	"			
	35		109	"	"		25	RL	109	TP	"			
163	20	RL	71.2	TP	"	212	21	RL	99.9	"	"			
165.2	2.8	4000	11.3	"	C		41	RL	175	TK	"			
	3.4	4000	13.7	"	"		216.3	2.8	4000	14.9	"	C		
	5	4000	20	"	H			4	4000	21.2	"	"		
		5500		"	"			6.5	4000	34	"	C/H		
	6	RL	23.8	"	"				5500		"	H		
	7.1	4000	28	"	"				6000		"	H		
		5500		"	"			8.2	4000	42.5	TP	H		
	9.5	4000	36.8	TP	H					5500		"	"	
	11	4000	42.3	"	"					6000		"	"	
	14.3	RL	53.8	"	"				12.7	4000	64.4	"	"	
	18.2	RL	66.6	"	"						5500		"	"
	21.9	RL	78.2	TK	"						6000		"	"
	30	RL	101	TP	"			170	10	RL	39.9	TK	"	
170	10	RL	39.9	TK	"	18.2			5500	89.8	"	"		

JIS シームレス鋼管

SUS304													
材質													
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上		
216.3	23	5500	111	TP	H	318.5	17.4	4000	131	TP	H		
	30	RL	139	TK	〃			5500		〃	〃		
220	22	RL	109	TP	〃	318.5	21.4	8000	158	〃	〃		
	25	RL	121	〃	〃			5500		185	〃	〃	
224	22	RL	111	〃	〃	318.5	33.3	5500	237	〃	〃		
	32	RL	153	TK	〃			6000		〃	〃		
	42	RL	190	TP	〃			340		35	6000	266	〃
232	16	RL	86.1	TK	〃	355.6	11.1	4000	95.3	〃	〃		
	21	RL	110	〃	〃			5500		〃	〃		
234	32	RL	161	〃	〃	355.6	19	4000	159	〃	〃		
236	23	RL	122	〃	〃			5500		〃	〃		
250	25	RL	140	〃	〃	355.6	35.7	5500	284	〃	〃		
	30	RL	164	〃	〃			406.4		12.7	4000	125	〃
267.4	4	4000	26.2	〃	C	406.4	12.7	5500	289	〃	〃		
	6.5	4000	42.2	〃	〃			5500		205	〃	〃	
		5500		〃	〃			30.9		5500	〃	〃	
	9.3	4000	59.8	〃	H								
		5500		〃	〃								
		8000		〃	〃								
	12.7	5500	80.6	〃	〃								
	15.1	4000	94.9	〃	〃								
		5500		〃	〃								
	21.4	5500	131	〃	〃								
25.4	6000	153	〃	〃									
28.6	5500	170	〃	〃									
300	30	6000	202	〃	〃								
318.5	4.5	4000	35.2	TP	C								
	6.5	4000	50.5	〃	〃								
		5500		〃	〃								
	10.3	4000	79.1	〃	H								
		5500		〃	〃								
	8000		〃	〃									

JIS シームレス鋼管

SUS304L											
材質											
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
4	1	4000	0.075	TP	C	27.2	5.5	5500	2.97	TP	C
10	1	4000	0.224	"	"	34	1.65	4000	1.33	"	"
13.8	1.2	4000	0.377	"	"	34	2.8	4000	2.18	"	H
		5500	0.499	"	"			5500	"	"	
	1.65	4000	0.588	"	"		3	4000	2.32	"	"
		5500	0.636	"	"			5500	"	"	
		4000	0.807	"	"			4000	2.59	"	"
17.3	1.65	4000	0.643	"	"	42.7	4.5	5500	"	"	
		5500	0.762	"	"			4000	3.31	"	"
	2	4000	0.859	"	"		6.4	5500	"	"	
		5500	"	"	4000			4.4	"	"	
		4000	1.12	"	"			5500	"	"	
5500	"	"	42.7	2.8	4000	2.78	"	"			
21.7	1.65	4000	0.824	"	"	48.6	3	5500	"	"	
		5500	1.03	"	"			4000	2.97	"	"
	2.1	4000	"	"	3.6		5500	"	"		
		5500	1.2	"			"	4000	3.51	"	"
		4000	"	"			5500	"	"		
	2.5	4000	1.32	"	"		4.9	4000	4.61	"	"
		5500	"	"	5500			"	"		
		4000	1.66	"	"			4000	5.79	"	"
5500	"	"	48.6	6.4	4000	"	"				
27.2	1.65	4000	1.05	"	"	48.6	1.65	4000	1.93	"	C
		5500	1.31	"	"			2.8	4000	2.32	"
	2.1	4000	"	"	3		5500		"	"	
		5500	1.54	"			"	4000	3.19	"	"
		4000	"	"			5500	"	"		
	2.5	4000	1.76	"	"		3.7	4000	4.14	"	"
		5500	"	"	5500			"	"		
		4000	2.26	"	"			4000	5.53	"	"
5500	"	"	48.6	5.1	4000	"	"				
2.9	4000	2.26	"	"	7.1	7.1	4000	7.34	"	"	
	5500	"	"	5500			"	"			
	4000	2.97	"	"			4000	"	"		
5500	"	"	48.6	7.1	4000	"	"				



JIS シームレス鋼管

SUS304L											
材質											
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
48.6	7.1	5500	7.34	TP	H	101.6	5.7	4000	13.6	TP	H
60.5	1.65	4000	2.42	"	C	114.3	8.1	5500		"	"
		4000	4.02	"	H			4000	18.9	"	"
	3.5	5500		"	"	3	4000	5.87	"	C	
		4000	4.97	"	"		4000	8.32	"	H	
	3.9	5500		"	"	4	5500		"	"	
		4000	5.5	"	"		4000	11	"	"	
	5.5	5500		"	"	6	5500		"	"	
		4000	7054	"	"		4000	16.2	"	"	
	8.7	5500		"	"	8.6	5500		"	"	
		4000	11.2	"	"		4000	22.6	"	"	
76.3	3	5500		"	"	13.5	13.5	5500		"	"
		4000	5.48	"	"			4000	33.9	"	"
	3.5	5500		"	"	3.4	5	4000	11.6	"	C
		4000	6.35	"	"			5500		"	"
	5.2	5500		"	"	6.6	6.6	4000	16.8	"	H
		4000	9.21	"	"			5500		"	"
	7	5500		"	"	9.5	9.5	4000	21.9	"	"
		4000	12.1	"	"			5500		"	"
	9.5	5500		"	"	5	5	4000	30.8	"	"
		4000	15.8	"	"			5500		"	"
89.1	3	5500		"	"	7.1	7.1	4000	20	"	"
		4000	6.43	"	"			5500		"	"
	4	5500		"	"	11	11	4000	28	"	"
		4000	8.48	"	"			5500		"	"
	5.5	5500		"	"	6.5	6.5	4000	42.3	"	"
		4000	11.5	"	"			5500		"	"
7.6	5500		"	"	8.2	8.2	4000	34	"	"	
	4000	15.4	"	"			5500		"	"	
11.1	5500		"	"	12.7	12.7	4000	42.5	"	"	
	4000	21.6	"	"			5500		"	"	
101.6	3	4000	7.37	"	"	4	4	4000	64.4	"	"
	4	4000	9.72	"	"			5500		"	"

JIS シームレス鋼管

SUS316												
材質												
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	
3	1	4000	0.05	TP	C	9.53	2	4000	0.378	TP	〃	
4	0.5	2000	0.044	〃	〃	10	0.5	2000	0.119	〃	〃	
		4000						4000				〃
	1	2000	0.08	〃	〃		1	2000	0.226	〃	〃	
		4000						4000				〃
5	1	4000	0.1	〃	〃	1.5	2000	0.32	〃	〃		
	1.5	4000	0.132	〃	〃		4000				〃	〃
6	0.5	2000	0.069	〃	〃	10.5	2	4000	0.401	〃	〃	
		4000						〃				〃
	1	2000	0.125	〃	〃		1.2	4000	0.28	〃	〃	
		4000						5500				〃
	1.5	4000	0.169	〃	〃		1.5	4000	0.338	〃	〃	
		4000						5500				〃
2	4000	0.201	〃	〃	1.7	4000	0.375	〃	〃			
	4000					5500				〃	〃	
6.35	0.89	2000	0.122	〃	〃	11	2.4	4000	0.487	〃	〃	
		4000						5500				〃
	1	2000	0.134	〃	〃		2	4000	0.451	〃	〃	
		4000						5500				〃
	1.5	4000	0.182	〃	〃		12	0.5	4000	0.144	〃	〃
4000		4000				〃			〃			
1.65	4000	0.194	〃	〃	1	2000	0.276	〃	〃			
	4000					4000				〃	〃	
7	1	4000	0.15	〃	〃	1.2	2000	0.325	〃	〃		
	1.5	4000	0.207	〃	〃		4000				〃	〃
8	1	4000	0.175	〃	〃	1.5	2000	0.395	〃	〃		
	1.5	4000	0.244	〃	〃		4000				〃	〃
	2	4000	0.301	〃	〃		4000				〃	〃
9	1	4000	0.201	〃	〃	2	4000	0.501	〃	〃		
	1.5	4000	0.282	〃	〃		4000				〃	〃
9.53	0.89	4000	0.193	〃	〃	2.5	4000	0.595	〃	〃		
		2000					4000				〃	〃
	1	2000	0.214	〃	〃	3	4000	0.677	〃	〃		
		4000					〃				〃	
	1.24	4000	0.258	〃	〃	12.7	0.89	4000	0.264	〃	〃	
		4000						2000				〃
	1.5	4000	0.302	〃	〃	1	4000	0.293	〃	〃		
4000		4000					〃				〃	
1.65	4000	0.326	〃	〃	1.2	4000	0.346	〃	〃			

JIS シームレス鋼管

SUS316												
材質												
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	
12.7	1.24	4000	0.356	TP	C	17	1.5	4000	0.583	TP	C	
	1.5	4000	0.421	"	"		17.3	1.65	4000	0.647	"	"
	1.65	2000	0.457	"	"			5500	"	"		
		4000	"	"	2			4000	0.767	"	"	
	2	4000	0.536	"	"			5500	"	"		
13	1	2000	0.301	"	"	2.3	4000	0.865	"	"		
		4000	"	"	5500		"	"				
13.8	1.2	4000	0.379	"	"	3.2	4000	1.13	"	"		
		5500	"	"	18		1.5	4000	0.62	"	"	
	1.65	4000	0.503	"		"	2	4000	0.802	"	"	
		5500	"	"		3	4000	1.13	"	"		
	2	4000	0.592	"	"	19	0.5	4000	0.232	"	"	
		5500	"	"	1.5		4000	0.658	"	"		
	2.2	4000	0.64	"	"		2	4000	0.852	"	"	
		5500	"	"	3		4000	1.2	"	"		
	3	4000	0.812	"	"	4	4000	1.5	"	"		
		5500	"	"	20	1	4000	0.476	"	"		
14	1	4000	0.326	"		"	1.5	4000	0.696	"	"	
		4000	0.47	"		"	2	4000	0.903	"	"	
	1.5	4000	0.602	"	"	4	4000	1.6	"	"		
		2	4000	0.602	"		"					
15	1	4000	0.351	"	"	21.7	1.65	4000	0.829	"	"	
	1.5	4000	0.508	"	"		2.1	4000	1.03	"	"	
	2	4000	0.652	"	"		2.5	4000	1.2	"	"	
	2.5	4000	0.783	"	"		5500	"	"			
15.88	1.5	4000	0.541	"	"	2.8	4000	1.33	"	"		
16	0.5	4000	0.194	"	"	5500	"	"				
		1	4000	0.376	"		"	3.7	4000	1.67	"	"
	1.5	4000	0.545	"	"	5500	"		"			
	2	4000	0.702	"	"	4.7	4000		2	"	"	
	2.5	2000	0.846	"	"	22	1	4000	0.526	"	"	
		4000	"	"	25		1	4000	0.602	"	"	
	3	4000	0.978	"	"	1.5	4000	0.884	"	"		

JIS シームレス鋼管

SUS316											
材質											
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
25	2	4000	1.15	TP	C	42.7	1.65	4000	1.7	TP	C
	3	4000	1.65	"	"		2	4000	2.04	"	"
25.4	2	4000	1.17	"	"	42.7	2.8	4000	2.8	"	C/H
27.2	1.65	4000	1.06	"	"		5500			"	"
	2.1	4000	1.32	"	"	3	4000	2.99	"	"	
27.2	2.5	4000	1.55	"	"	42.7	5500			"	"
		5500		"	"		3.6	4000	3.53	"	"
27.2	2.9	4000	1.77	"	"	42.7	5500			"	"
		5500		"	"		4.9	4000	4.64	"	"
27.2	3.9	4000	2.28	"	"	42.7	5500			"	"
		5500		"	"		6.4	4000	5.82	"	"
27.2	5.5	4000	2.99	"	"	42.7	7.1	4000	6.34	"	"
		5500		"	"		5500			"	"
30	3	4000	2.03	"	"	42.7	10	4000	8.2	"	"
	5	4000	3.13	"	"		45	12	4000	9.93	"
32	5	4000	3.38	"	"	42.7	12.5	RL	10.2	"	"
34	1.65	4000	1.34	"	"		48.6	1.65	4000	1.94	"
	34	2.8	4000	2.19	"	"	42.7	2.8	4000	3.21	"
		5500		"	"	5500				"	"
34	3	4000	2.33	"	"	42.7	3	4000	3.43	"	"
		5500		"	"		5500			"	"
34	3.4	4000	2.61	"	"	42.7	3.7	4000	4.16	"	"
		5500		"	"		5500			"	"
34	4.5	4000	3.33	"	H	42.7	5.1	4000	5.56	"	"
		5500		"	"		5500			"	"
34	6.4	4000	4.43	"	"	42.7	7.1	4000	7.39	"	"
		5500		"	"		52	10	RL	10.5	"
38	1.5	4000	1.37	"	C	53	13.5	RL	13.4	TK	"
	4	4000	3.41	"	H	42.7	56	10	RL	11.5	TP
38	6	4000	4.81	"	"		12	RL	13.2	TP	H
		5500		"	"	57	6.5	4000	8.23	"	"
40	10	4000	7.52	"	"	42.7	8	RL	9.83	"	"

JIS シームレス鋼管

SUS316													
材質													
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上		
60.5	1.65	4000	2.43	TP	C	76.3	5.2	4000	9.27	TP	H		
	2	4000	2.93	"	"		5500	"	"				
	2.8	4000	4.05	"	H		7	4000	12.2	"	"		
		5500	"	"	5500		"	"					
	3	4000	4.32	"	"		9.5	4000	15.9	"	"		
		5500	"	"	5500		"	"					
	3.5	4000	5	"	"		13.5	4000	21.3	"	"		
		5500	"	"	5500		"	"					
	3.9	4000	5.53	"	"		15	4000	23.1	"	"		
		5500	"	"	18		RL	26.3	"	"			
	5.5	4000	7.58	"	"		20	RL	28.2	"	"		
		5500	"	"	80		12	4000	20.5	"	"		
	8.7	4000	11.3	"	"		20	RL	30.1	"	"		
		5500	"	"	85		12.5	4000	22.7	"	"		
	11.1	4000	13.7	"	"		89.1	3	4000	6.48	"	"	
	15	4000	17.1	"	"			5500	"	"			
	63.5	11	6000	14.5	"		"		4	4000	8.53	"	"
		13	4000	16.5	"		"		5500	"	"		
65	10	RL	13.8	"	"		5.5	4000	11.5	"	"		
	15	6000	18.8	"	"		5500	"	"				
66	9	RL	12.9	"	"		7.6	4000	15.5	"	"		
67	12	4000	16.5	"	"		5500	"	"				
70	12	4000	17.4	"	"		11.1	4000	21.7	"	"		
	17.5	RL	23	"	"		15	RL	27.9	"	"		
71	17.5	RL	23.5	"	"	90	15	4000	28.2	"	"		
72	17.5	4000	23.9	TK	"		20	RL	35.1	"	"		
75	12	4000	19	TP	"	95	15	RL	30.1	"	"		
76.3	2.1	4000	3.91	"	C		22.5	RL	40.9	"	"		
	3	4000	5.51	"	C/H	100	20	RL	40.1	"	"		
		5500	"	"	C/H	101.6	3	4000	7.42	TP	H		
	3.5	4000	6.39	"	H		4	4000	9.79	"	"		
	5500	"	"	"		5.7	4000	13.7	"	"			

JIS シームレス鋼管

SUS316											
材質											
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
101.6	8.1	4000	19	TP	H	165.2	5	5500	20.1	TP	H
106	18	RL	39.7	"	"		7.1	4000	28.1	"	"
107	19.5	RL	42.8	"	"			5500		"	"
110	15	RL	35.7	"	"		11	4000	42.5	"	"
114.3	2.1	4000	5.91	"	C	170	15	RL	58.3	"	"
	3	4000	8.37	"	H	180	15	RL	62	TK	"
		5500		"	"	216.3	4	4000	21.3	TP	C
	4	4000	11.1	"	"		6.5	4000	34.2	"	"
		5500		"	"		8.2	4000	42.8	"	"
	6	4000	16.3	"	"						
		5500		"	"						
	8.6	4000	22.8	"	"						
		5500		"	"						
	11.1	4000	28.7	"	"						
	13.5	4000	34.1	"	"						
116	18	RL	44.2	"	"						
120	15	RL	39.5	"	"						
122.5	8.6	RL	24.6	"	"						
125	10	RL	28.8	"	"						
135	10	RL	31.3	TK	"						
	20	RL	57.7	"	"						
139.8	5	4000	16.9	TP	"						
		5500		"	"						
	6.6	4000	22	"	"						
		5500		"	"						
	9.5	4000	31	"	"						
	15.9	RL	49.4	"	"						
140	20	RL	60.2	"	"						
145	20	RL	62.7	TK	"						
150	15	RL	50.8	TP	"						
165.2	3.4	4000	13.8	"	C						
	5	4000	20.1	"	H						

JIS シームレス鋼管

SUS316L													
材質													
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上		
2	0.5	2000	0.019	TP	C	10	2	4000	0.401	TP	C		
3	1	4000	0.05	"	"	10	2.5	4000	0.47	"	"		
4	0.5	2000	0.44	"	"	10.5	1	4000	0.238	"	"		
	1	2000	0.075	"	"		1.2	4000	0.28	"	"		
5	1	4000	0.1	"	"			5500		"	"		
	1.5	4000	0.132	"	"		1.5	4000	0.338	"	"		
6	0.5	4000	0.069	"	"			5500		"	"		
	1	2000	0.125	"	"		1.7	4000	0.375	"	"		
		4000		"	"			5000		"	"		
	1.5	4000	0.169	"	"			5500		"	"		
	2	4000	0.201	"	"		2	4000	0.426	"	"		
6.35	0.89	2000	0.122	"	"		2.4	4000	0.487	"	"		
		4000		"	"			5500		"	"		
	1	2000	0.134	"	"		11	2	4000	0.451	"	"	
		4000		"	"		12	1	4000	0.276	"	"	
1.5	4000	0.182	"	"	1.2	4000		0.325	"	"			
8	0.5	4000	0.094	"	"		1.5	4000	0.395	"	"		
		2000	0.175	"	"			2	4000	0.501	"	"	
		4000		"	"			2.5	4000	0.595	"	"	
	1.5	2000	0.244	"	"		3	4000	0.677	"	"		
		4000		"	"			12.7	1	4000	0.293	"	"
		2	4000	0.301	"				"	1.2	4000	0.346	"
		2.5	4000	0.345	"			"	1.5	4000	0.421	"	"
9	1	4000	0.201	"	"		1.65	4000	0.457	"	"		
9.53	0.89	4000	0.193	"	"		2	4000	0.536	"	"		
		2000	0.214	"	"			13.8	1.2	4000	0.379	"	"
	4000		"	"			5500			"	"		
	1.5	4000	0.302	"	"		1.65	4000	0.503	"	"		
1.65	4000	0.326	"	"		5500		"	"				
10	0.5	4000	0.119	"	"		2	4000	0.592	"	"		
	1	4000	0.226	"	"		5500		"	"			
	1.5	4000	0.32	"	"	2.2	4000	0.64	"	"			

JIS シームレス鋼管

SUS316L											
材質											
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
13.8	2.2	5500	0.64	TP	C	19	2	4000	0.852	TP	C
	3	4000	0.812	"	"		3	4000	1.2	"	"
		5500		"	"		20	1	4000	0.476	"
14	1	4000	0.326	"	"	1.5		4000	0.696	"	"
	2	4000	0.602	"	"	21.7	1.65	4000	0.829	"	"
	2.5	4000	0.721	"	"		2.1	4000	1.03	"	"
	3	4000	0.827	"	"			5500		"	"
15	1	4000	0.351	"	"		2.5	4000	1.2	"	"
	2.5	4000	0.783	"	"		5500		"	"	
	3	4000	0.903	"	"	2.8	4000	1.33	"	"	
16	1	4000	0.376	"	"		5500		"	"	
	1.2	4000	0.445	"	"		6000		"	"	
	1.5	4000	0.545	"	"	3.7	4000	1.67	"	"	
	2	4000	0.702	"	"		5500		"	"	
17.3	1.2	4000	0.484	"	"		6000		"	"	
	1.5	4000	0.594	"	"	4.7	4000	2	"	"	
		5500		"	"		5500		"	"	
	1.65	4000	0.647	"	"	22	3	4000	1.43	"	"
		5500		"	"	25	1	4000	0.602	"	"
	2	4000	0.767	"	"	2	4000	1.15	"	"	
		5500		"	"	3	4000	1.65	"	"	
	2.3	4000	0.865	"	"	25.4	2	4000	1.17	"	"
		5500		"	"	27.2	1.65	4000	1.06	"	"
18	1	4000	0.426	"	"		2.1	4000	1.32	"	"
	1.5	4000	0.62	"	"		5500		"	"	
	2	4000	0.802	"	"	2.5	4000	1.55	"	"	
	2.5	4000	0.971	"	"	2.9	4000	1.77	"	"	
19	0.5	4000	0.232	"	"		5500		"	"	
	1	4000	0.451	"	"	3.9	4000	2.28	"	"	
	1.5	4000	0.658	"	"	5.5	4000	2.99	"	"	



JIS シームレス鋼管

SUS316L											
材質											
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
27.2	5.5	5500	2.99	TP	C	42.7	4.9	5500	4.64	TP	H
	7.8	4000	3.79	"	"		6.4	4000	5.82	"	"
		5500		"	"			5500		"	"
30	1	4000	0.727	"	"	48.6	1.65	4000	1.94	"	C
	1.5	4000	1.07	"	"		2	4000	2.34	"	"
	3	4000	2.03	"	"		2.8	4000	3.21	"	H
34	1.65	4000	1.34	"	"			5500		"	"
	2	4000	1.6	"	"	3	4000	3.43	"	"	
	2.8	4000	2.19	"	"			5500		"	"
		5500		"	"	3.7	4000	4.16	"	"	
		6000		"	"		5500		"	"	
	3	4000	2.33	"	"	5.1	4000	5.56	"	"	
		5500		"	"		5500		"	"	
	3.4	4000	2.61	"	"	6	4000	6.41	"	"	
		5500		"	"	7.1	4000	7.39	"	"	
		6000		"	"		5500		"	"	
	4.5	4000	3.33	"	H	10.2	4000	9.82	"	"	
		5500		"	"		5500		"	"	
		6000		"	"	50.8	2	4000	2.45	"	C
	6.4	4000	4.43	"	"		3	4000	3.6	"	H
		5500		"	"	56	8	4000	9.63	"	"
9.1	4000	5.68	"	C	60.5	1.65	4000	2.43	"	C	
38	2	4000	1.81	"	"		2	4000	2.93	"	"
							2.8	4000	4.05	"	H
42.7	1.65	4000	1.7	"	"			5500		"	"
	2	4000	2.04	"	"			5500		"	"
	2.8	4000	2.8	"	H	3	4000	4.32	"	"	
		5500		"	"	3.5	4000	5	"	"	
	3	4000	2.99	"	"		5500		"	"	
		5500		"	"		6000		"	"	
	3.6	4000	3.53	"	"	3.9	4000	5.53	"	"	
		5500		"	"		5500		"	"	
4.9	4000	4.64	"	"		6000		"	"		

JIS シームレス鋼管

SUS316L													
材質													
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上		
60.5	5.5	4000	7.58	TP	H	89.1	5.5	6000	11.5	TP	H		
		5500		"	"			7.6	4000	15.5	"	"	
		6000		"	"				5500		"	"	
	8.7	4000	11.3	"	"		11.1	4000	21.7	"	"		
		5500		"	"			5500		"	"		
	11.1	4000	13.7	TP	H		15.2	4000	28.2	"	"		
		15	4000	17.1	"			"	90	15	4000	28.2	"
63.5	2	4000	3.08	"	C	95	22.5	RL	40.9	"	"		
	3	4000	4.55	"	H	101.6	2.1	4000	5.24	"	C		
73	5.2	4000	8.84	"	"			3	4000	7.42	"	H	
		14	RL	20.7	"				"	4	5500		"
76.3	2.1	4000	3.91	"	C	4	4000	9.79	"		"		
		3	4000	5.51	"		H	5.7	5500		"	"	
	3.5	4000	5500		"	"	5.7		4000	13.7	"	"	
			5500		"	"		8.1	5500		"	"	
			5500		"	"			4000	19	"	"	
	5.2	4000	5500		"	"	12.7	4000	5500		"	"	
			5500		"	"			25	4000	28.3	"	"
5500				"	"	RL				48	"	"	
7	4000	5500		"	"	114.3	2.1	4000	5.91	"	C		
		5500		"	"			3	4000	8.37	"	C/H	
		5500		"	"				5500		"	H	
9.5	4000	5500		"	"	4	4000	5500		"	"		
		5500		"	"			4	4000	11.1	"	"	
82.6	8	RL	16.6	"	"	89.1	2.1	5500		"	"		
89.1	2.1	4000	4.58	"	C			3	4000	5500		"	"
		5500		"	"					6	4000	16.3	"
		5500		"	"		5500					"	"
4	4000	5500		"	"		8.6	4000	5500		"	"	
		5500		"	"				11.1	4000	22.8	"	"
5.5	4000	5500		"	"		11.1	4000		5500		"	"
		5500		"	"	13.5				4000	28.7	"	"
		5500		"	"				4000	34.1	"	"	
5.5	4000	5500		"	"	20	RL	4000	47.3	"	"		
		5500		"	"			116	18	RL	44.2	"	"

JIS シームレス鋼管

SUS316L												
材質												
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	
118	19	RL	47.2	TP	H	190.7	20	RL	85.6	TP	H	
120	25	RL	59.5	"	"	204	32	RL	138	"	"	
126	15.9	RL	43.9	"	"	212	21	RL	101	"	"	
132	30.5	RL	77.6	"	"	216.3	2.8	4000	15	"	C	
139.8	2.8	4000	9.62	"	C	216.3	4	4000	21.3	"	"	
	3.4	4000	11.6	"	"		6.5	4000	34.2	"	C/H	
	5	4000	16.9	"	C/H		5500		"	"	"	
		5500		"	C/H		8.2	4000	42.8	"	"	
	6.6	4000	22	"	H		5500		"	H	"	
		5500		"	"		12.7	4000	64.8	"	"	
	9.5	4000	31	"	"		5500		"	"	"	
	12.7	RL	40.5	"	"		18.2	5500	90.4	"	"	
	15.9	RL	49.4	"	"		23	RL	111	"	"	
	140	20	RL	60.2	"		"	224	22	RL	111	"
30		RL	82.7	TK	"	42	RL		192	"	"	
35		RL	92.1	TP	"	232	16		RL	86.6	"	"
150	25	RL	78.3	"	"	250	25	RL	141	"	"	
152.4	9.5	4000	34	"	"	267.4	4	4000	26.4	"	C	
165.2	2.8	4000	11.4	"	C	267.4	6.5	4000	42.5	"	"	
	3.4	4000	13.8	"	"		5500		"	"	"	
	5	4000	20.1	"	C		9.3	4000	60.2	"	H	
		5500		"	"		5500		"	"	"	
	7.1	4000	28.1	"	H		12.7	5500	81.1	"	"	
		5500		"	"		15.1	4000	95.5	"	"	
	11	4000	42.5	"	"		5500		"	"	"	
	14.3	RL	54.1	"	"		28.6	5500	171	"	"	
	30	RL	102	"	"		318.5	4.5	4000	35.4	"	C
	170	15	RL	58.3	"		"	6.5	4000	50.8	"	"
180	20	RL	80.2	"	"	5500		"	"	"		
	30	RL	113	"	"	10.3	4000	79.6	"	H		
190	15	RL	65.8	"	"	5500		"	"	"		
	20	RL	85.2	"	"	17.4	4000	131	"	"		

JIS シームレス鋼管

SUS316L											
材質											
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
318.5	17.4	5500	131	TP	H						
	25.4	5500	187	"	"						
355.6	11.1	4000	95.9	"	"						
		5500		"	"						
	19	4000	160	"	"						
		5500		"	"						
	35.7	6000		"	"						
		5500	286	"	"						
406.4	12.7	5500	125	"	"						
	21.4	5500	207	TP	H						
	30.9	5500	291	"	"						

JIS シームレス鋼管

SUS310S												
材質												
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	
10	1	4000	0.226	TP	C	34	3	5500	2.33	TP	C	
10.5	1.5	4000	0.338	"	"	34	3.4	4000	2.61	"	"	
	1.7	4000	0.375	"	"		5500	"	"			
	2.4	4000	0.487	"	"		4.5	4000	3.33	"	"	
13.8	1.2	4000	0.379	"	"	34	5500	"	"			
	1.65	4000	0.503	"	"		6.4	4000	4.43	"	"	
	2	4000	0.592	"	"		5500	"	"			
	2.2	4000	0.64	"	"		42.7	2.8	4000	2.8	"	"
3	4000	0.812	"	"	3	4000		2.99	"	"		
14	1	4000	0.326	"	"	42.7	5500	"	"			
17.3	2	4000	0.767	"	"		3.6	4000	3.53	"	H	
	2.3	4000	0.865	"	"		5500	"	"			
	3.2	4000	1.13	"	"	4.9	4000	4.64	"	"		
21.7	2.1	4000	1.03	"	"	42.7	5500	"	"			
	2.5	4000	1.2	"	"		6.4	4000	5.82	"	"	
	2.8	4000	1.33	"	"		48.6	2.8	4000	3.21	"	C
	5500	"	"	3	4000			3.43	"	"		
	3.7	4000	1.67	"	"		5500	"	"			
	5500	"	"	3.7	4000		4.16	"	"			
4.7	4000	2	"	"	5500	"	"					
27.2	2.1	4000	1.32	"	"	48.6	5.1	4000	5.56	"	H	
		5500	"	"	5500		"	"				
	2.5	4000	1.55	"	"		7.1	4000	7.39	"	"	
	5500	"	"	50.8	4		4000	4.69	"	"		
	2.9	4000	1.77		"		"	60.5	2.8	4000	4.05	"
	34	2.8	4000	2.19	"		"	60.5	3	4000	4.32	"
5500			"	"	3.5	4000	5		"	"		
5500		"	"	5500	"	"						
5.5		4000	2.99	"	"	3.9	4000		5.53	"	H	
34	2.8	4000	2.19	"	"	60.5	5500	"	"			
	3	4000	2.33	"	"		5.5	4000	7.58	"	"	

JIS シームレス鋼管

SUS310S												
材質												
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	
60.5	5.5	5500	7.58	TP	H	139.8	9.5	RL	31	TP	C	
	8.7	4000	11.3	"	"		165.2	5	4000	20.1	"	"
		5500	"	"	7.1			RL	28.1	"	"	
76.3	3	4000	5.51	"	"							
	3.5	4000	6.39	"	"							
	5.2	4000	9.27	"	"							
		5500	"	"								
	7	4000	12.2	"	"							
		5500	"	"								
9.5	4000	15.9	"	"								
86	4	RL	8.22	"	"							
89.1	3	4000	6.48	"	"							
		5500	"	"								
	4	4000	8.53	"	"							
		5500	"	"								
	5.5	4000	11.5	"	"							
		5500	"	"								
	7.6	4000	15.5	"	"							
11.1	4000	21.7	"	"								
101.6	4	4000	9.79	"	"							
	5.7	4000	13.7	"	"							
	8.1	4000	19	"	"							
	12.7	RL	28.3	"	"							
114.3	3	4000	8.37	"	C							
	4	4000	11.1	"	"							
		5500	"	"								
	6	4000	16.3	"	H							
		5500	"	"								
	8.6	4000	22	"	"							
13.5	RL	34.1	"	"								
139.8	5	4000	16.9	"	C							
	6.6	4000	22	"	"							

JIS シームレス鋼管

SUS321											
材質											
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上	外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
12	1.5	4000	0.392	TP	C						
	2.5	4000	0.592	"	"						
21.7	2.8	4000	1.32	"	"						
	3.7	4000	1.66	"	"						
	4.7	4000	1.99	"	"						
27.2	2.1	4000	1.31	"	"						
	2.5	4000	1.54	"	"						
	2.9	4000	1.76	"	"						
	3.9	4000	2.26	"	"						
	5.5	4000	2.97	"	"						
34	2.8	4000	2.18	"	H						
	3	4000	2.32	"	"						
	3.4	4000	2.59	"	"						
42.7	3.6	4000	3.51	"	"						
	4.9	4000	4.61	"	"						
	6.4	4000	5.79	"	"						
48.6	3	4000	3.41	"	"						
	3.7	4000	7.34	"	"						
60.5	2.8	4000	4.02	"	"						
	3.5	4000	4.97	"	"						
	3.9	5500	5.5	"	"						
	5.5	5500	7.54	"	"						
76.3	3	4000	5.48	"	"						
	3.5	4000	6.35	"	"						
	5.2	4000	9.21	"	"						
89.1	3	4000	6.43	"	"						
	4	4000	8.48	"	"						
114.3	3	4000	8.32	"	"						
	4	4000	11	"	"						
	6	4000	16.2	"	"						
139.8	5	4000	11.9	"	"						