

JIS シームレス鋼管

SUS304 BA						材質	SUS304 BA					
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上		外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
3	0.5	2000	0.031	TP	C	SUS304 BA	12.7	1	4000	0.291	TP	C
3.18	0.5	2000	0.33	"	"		1.24	2000	0.354	"	"	
4	0.5	2000	0.044	"	"		1.65	4000	"	"	"	
	1	2000	0.075	"	"			4000	0.454	"	"	
5	0.5	2000	0.056	"	"		14	1	4000	0.324	"	"
	1	2000	0.1	"	"		15.88	1.24	4000	452	"	"
6	1	2000	0.125	"	"		16	1	2000	0.374	"	"
		4000	"	"	4000				"	"		
6.35	0.5	2000	0.073	"	"		19.05	1	2000	0.45	"	"
		4000	"	"	4000				"	"		
	0.89	2000	0.121	"	"			1.24	2000	0.55	"	"
		4000	"	"	4000				"	"		
	1	2000	0.133	"	"			1.65	2000	0.715	"	"
		4000	"	"	4000				"	"		
1.24	2000	0.158	"	"	20		1	4000	0.473	"	"	
	4000	"	"	25.4	1.65		4000	0.976	"	"		
8	0.5	2000	0.093	"	"		SUS304 BA					
		4000	"	"								
	1	2000	0.174	"	"							
4000		"	"									
9.53	1	2000	0.212	"	"							
		4000	"	"								
	1.24	2000	0.256	"	"							
		4000	"	"								
1.65	4000	0.324	"	"								
10	1	2000	0.224	"	"							
		4000	"	"								
	1.5	2000	0.318	"	"							
4000		"	"									
12	1	2000	0.274	"	"							
		4000	"	"								
12.7	1	2000	0.291	"	"							

JIS シームレス鋼管

SUS316 BA						材質	SUS316L BA					
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上		外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
3.18	0.5	2000	0.033	TP	C	3.18	0.5	2000	0.033	TP	C	
	0.72	2000	0.044	"	"		0.72	2000	0.04	"	"	
	0.89	2000	0.051	"	"		6	1	2000	0.125	"	"
4	0.5	2000	0.044	"	"	4000			"	"		
		1	2000	0.075	"	"	6.35	1	2000	0.134	"	"
6	0.5	2000	0.069	"	"	4000			"	"		
		1	2000	0.125	"	"	1.24	2000	0.159	"	"	
			4000	"	"	8		1	2000	0.175	"	"
6.35	0.89	4000	0.122	"	"		4000		"	"		
		1	2000	0.134	"	"	9.53	1	2000	0.214	"	"
			4000	"	"	4000			"	"		
1.24	4000	0.159	"	"	1.24	2000	0.258	"	"			
	8	1	2000	0.175		"	"	10	1	2000	0.226	"
4000			"	"	4000	"	"					
9.53	1	2000	0.214	"	"	12	1	2000	0.276	"	"	
		4000	"	"	4000			"	"			
		1.24	4000	0.258	"			"	12.7	1	2000	0.293
10	1	2000	0.226	"	"	4000	"	"				
		4000	"	"	1.24	2000	0.356	"			"	
12	1	2000	0.276	"	"	4000	"	"				
		4000	"	"	1.65	4000	0.457	"	"			
		12.7	1	2000		0.293	"	"	4000	0.326	"	"
4000	"			"	19.05	1.24	4000	0.554	"	"		
1.24	2000	0.356	"	"			1.65	4000	0.72	"	"	
	4000	"	"	13.8	1.2	4000	0.379	"	"			
1.65	4000	0.457	"			"						
	15.88	1.5	4000			0.541	"	"				
17.3	1.2	4000	0.484	"	"							
19.05	1.2	4000	0.537	"	"							
		1.24	4000	0.554	"	"						

JIS シームレス鋼管

SUS304(コイル)						材質	SUS316(コイル)					
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上		外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
3	0.5	30m	0.031	TP	C	6	1	30m	0.125	TP	C	
3.18	0.5	30m	0.033	"	"	8	1	30m	0.175	"	"	
	0.7	30m	0.043	"	"							
6	1	30m	0.125	"	"	10	1	30m	0.226	"	"	
		50m										"
6.35	1	30m	0.133	"	"	12	1	30m	0.276	"	"	
		50m										"
8	1	30m	0.174	"	"							
		50m				"	"					
9.53	1	30m	0.212	"	"							
		50m				"	"					
10	1	30m	0.224	"	"							
		50m				"	"					
	1.3	50m	0.282	"	"							
12	1	30m	0.274	"	"							
		50m				"	"					
	1.3	50m	0.346	"	"							
12.7	1	30m	0.291	"	"							
		50m				"	"					

JIS シームレス鋼管

SUS316L EP						材質						
外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上		外径 (mm)	肉厚 (mm)	長さ	質量 (Kg/m)	規格	仕上
3.18	0.72	2000	0.044	TP	S							
6.35	1	2000	0.159	"	S							
		4000			S							
9.53	1	2000	0.214	"	S							
		4000			S							
12.7	1	2000	0.293	"	S							
		4000			S							
	1.24	2000	0.356	"	S							
4000		S										